FREEDOM arm



Portable go-to measurement where it benefits you most

Advanced technology with multi-functional capability

The FREEDOM arm range of 6 axis and 7 axis portable arms are designed for practicality and versatility - with touch probe and laser scanner technology for quality control, on-machine verification, reverse engineering or 3D modelling.

Model shown: FREEDOM Classic Scan 7 axis portable measuring arm.

Contact us now to book your demonstration

www.LKmetrology.com

TECHNICAL DATA | **Portable Arm**

	FREEDOM CLASSIC 6 axis - touch probe only **standard accuracy**		**FREEDOM SELECT** 6 axis - touch probe only **high accuracy**		**FREEDOM ULTIMATE** 6 axis - touch probe only **ultra accuracy**		**FREEDOM CLASSIC** *SCAN* 7 axis - probe and laser **standard accuracy**		**FREEDOM SELECT** *SCAN* 7 axis - probe and laser **high accuracy**		**FREEDOM ULTIMATE** *SCAN* 7 axis - probe and laser **ultra accuracy**	
Size	Reach[1]	Accuracy[2]	Reach[1]	Accuracy[2]	Reach[1]	Accuracy[2]	Reach[1]	Accuracy[2]	Reach[1]	Accuracy[2]	Reach[1]	Accuracy[2]
20	2230	0.040	2230	0.023	-	-	2480	0.043	2480	0.029	-	-
	(87.8)	(0.0016)	(87.8)	(0.0009)	-	-	(97.6)	(0.0017)	(97.6)	(0.0011)	-	-
25	2730	0.046	2730	0.028	2730	0.026	2980	0.048	2980	0.031	2980	0.029
	(107.5)	(0.0018)	(107.5)	(0.0011)	(107.5)	(0.0010)	(117.3)	(0.0019)	(117.3)	(0.0012)	(117.3)	(0.0011)
30	3230	0.067	3230	0.042	3230	0.039	3480	0.078	3480	0.057	3480	0.053
	(127.2)	(0.0026)	(127.2)	(0.0017)	(127.2)	(0.0015)	(137.0)	(0.0031)	(137.0)	(0.0022)	(137.0)	(0.0021)
35	3730	0.085	3730	0.055	3730	0.052	3980	0.092	3980	0.069	3980	0.064
	(146.9)	(0.0033)	(146.9)	(0.0022)	(146.9)	(0.0020)	(156.7)	(0.0036)	(156.7)	(0.0027)	(156.7)	(0.0025)
40	4230	0.100	4230	0.067	4230	0.063	4480	0.114	4480	0.084	4480	0.078
	(166.5)	(0.0039)	(166.5)	(0.0026)	(166.5)	(0.0025)	(176.4)	(0.0045)	(176.4)	(0.0033)	(176.4)	(0.0031)
45	4730	0.120	4730	0.080	4730	0.074	4980	0.158	4980	0.113	4980	0.104
	(186.2)	(0.0047)	(186.2)	(0.0031)	(186.2)	(0.0029)	(196.1)	(0.0062)	(196.1)	(0.0044)	(196.1)	(0.0041)

[1] Maximum Reach specified as a spherical diameter using a 50mm long probe.
[2] Touch probe accuracy specification E UNI maximum permissible longitudinal error of measurement according to ISO 10360-12:2016.
FREEDOM ULTIMATE and FREEDOM ULTIMATE SCAN not available in 2.0m size. Refer to FREEDOM arm datasheet for other Technical Data.

mm (inch)

TECHNICAL DATA | **Laser Scanner**



MODELMAKER H120

Accuracy[3]	7 µm	0.00028 inch
Line width	120 mm	4.7 inch
Measuring range	100 mm	4.1 inch
Stand-off	80 mm	3.1 inch
Resolution (min.)	35 µm	0.0014 inch
Frame rate (max.)	450 Hz	
Point per line (max.)	2,000	
Laser adjustment	ESP4 each point in real-time	
Warm-up	0 seconds	
Weight	0.5kg	1.1lbs
Laser type	Class 2	

[3] Laser scanner accuracy according to manufacturer's test procedure.

TECHNICAL DATA | **Control Pack**



	CP-C control pack (included as standard)	**CP-W control pack** (upgrade option)
Probe	√	√
Laser scanner	√	√
Ethernet connection	√	√
USB* connection	√	√
Wireless connection	-	√
Mains power	√	√
Battery power	-	√

*USB connection via included USB to Ethernet cable adapter.

TECHNICAL DATA | **Supports**

Portable Metrology Tripod



- Ultra-stable tensioned tripod
- 780mm-1140mm (31"-45") height range
- Aircraft grade aluminium tubes
- Level gauge
- Bottom weight hook

Rolling Metrology Stand



- Heavy duty stand
- 710mm-1440mm (28"-57") height range
- Air cushioned cylinder
- Foot pedal lock
- Laptop arm option

Rolling Metrology Cart



- Granite work top
- 610x910mm (24"x36") or 710x1220mm (28" x 48") table
- Threaded inserts
- Clamping kit included
- Laptop arm option

...we are metrology

LK Metrology Ltd. | East Midlands Airport, Castle Donington, Derby, DE74 2SA | Telephone: 01332 811138 | Email: Sales.UK@LKmetrology.com

www.LKmetrology.com

Copyright © 2020 LK Metrology. All Rights Reserved.